

DECLARATION OF PERFORMANCE FOR THE PRODUCT UX180 - H6 1301 - CPR - 1279

Unique identification code of the product type:

High-Tensile Steel Wire Mesh System UX180 - H6, System Drawing GD-1008.1 / 1008.2 / 1008.3

Intended use:

Retaining of debris flow with maximum impact pressure of 180 kN/m²

Manufacturer:

Geobrugg AG
Aachstrasse 11
8590 Romanshorn
SWITZERLAND

System of assessment and verification of consistency of performance (AVCP):

System 1

European Assessment:

European Organisation for Technical Approvals: EAD 340020-00-0106

European Technical Assessment: ETA 17/0271

CE Certificate of Conformity: 1301 - CPR - 1279

Notified body: TSÚS, Building Testing and Research Institute, Bratislava, Slovak Republic (No 1301)

Declared performance:

See ETA 17/0271 Table 1

Swiss Guideline / Federal Office of the Environment:

Specific Technical Documentation:

Manual incl. System drawing, maintenance manual, anchor forces

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Armin Roduner, Technical Department

03.04.2018

Signature:





17

GeobruGG AG
Aachstrasse 11, 8590 Romanshorn, SWITZERLAND

Debris Flow Protection Barrier
UX180 - H6

Dynamic pressure resistance: 180 kN/m²

Flexible Kits for retaining debris flows and shallow landslides/open hill debris flow

ETA 17/0271
1301 - CPR - 1279
EAD 340020-00-0106
Notified body: TSÚS (No. 1301)

www.geobruGG.com