

DECLARATION OF PERFORMANCE FOR THE PRODUCT RXE-3000 1301 - CPR - 1022

Unique identification code of the product type:

Rockfall Protection Barrier RXE-3000, System Drawing GS-1157 / GS-1158

Intended use:

Falling Rock Protection Kit for use in civil engineering works to stop moving rock blocks with maximum energy of 3000 kJ

Manufacturer:

Geobrugg AG
Aachstrasse 11
8590 Romanshorn
SWITZERLAND

System of assessment and verification of consistency of performance (AVCP):

System 1

European Assessment:

European Organisation for Technical Approvals: ETAG 027

European Technical Assessment: ETA 14/0362

Certificate of constancy of performance: 1301 - CPR - 1022

Notified body: TSÚS, Building Testing and Research Institute, Bratislava, Slovak Republic (No 1301)

Declared performance:

Energy level classification: 6

Maximum Energy Level (MEL): 3000 kJ

Service Energy Level (SEL): 1000 kJ

Classification for residual height for MEL: Cat. A (> 50%)

Swiss Guideline / Federal Office of the Environment:

Test Certificate No. FOEN S 14-4 from 20.10.2014

Specific Technical Documentation:

Manual incl. System drawing, maintenance manual, anchor forces

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Armin Roduner, Technical Department

03.04.2018

Signature:





14

Geobrugg AG
Aachstrasse 11, 8590 Romanshorn, SWITZERLAND

Rockfall Protection Barrier
RXE-3000

Energy level classification: 6

Classification for residual height for MEL: Cat. A (> 50%)

**Falling Rock Protection Kit for use in civil engineering works to stop moving rock blocks
with maximum energy of 3000 kJ**

ETA 14/0362
1301 - CPR - 1022

ETAG 027
Notified body: TSÚS (No. 1301)

www.geobrugg.com