

# DECLARATION OF PERFORMANCE FOR THE PRODUCT TECCO® G65/3 1301 - CPR - 1274

## Unique identification code of the product type:

High-Tensile Steel Wire Mesh System TECCO® G65/3, System Drawing GE-1003

## Intended use:

High tensile steel mesh system for retaining of unstable slopes.

## Manufacturer:

Geobrugg AG  
Aachstrasse 11  
8590 Romanshorn  
SWITZERLAND

## System of assessment and verification of consistency of performance (AVCP):

System 1

## European Assessment:

European Organisation for Technical Approvals: EAD 230025-00-0106

European Technical Assessment: ETA 17/0118

CE Certificate of Conformity: 1301 - CPR - 1274

Notified body: TSÚS, Building Testing and Research Institute, Bratislava, Slovak Republic (No 1301)

## Declared performance:

Tensile strength: 150 kN/m

Bearing Resistance against Puncturing: 180 kN (P33) / 240 kN (P66)

Bearing Resistance against Slope-Parallel Tensile Stress: 30 kN (P33) / 45 kN (P66)

## Swiss Guideline / Federal Office of the Environment:

## Specific Technical Documentation:

Manual incl. System drawing, technical data sheet

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Armin Roduner, Technical Department

25.04.2019

Signature:





**19**

**Geobrugg AG**  
**Aachstrasse 11, 8590 Romanshorn, SWITZERLAND**

**High-Tensile Steel Wire Mesh System**  
**TECCO® G65/3**

**Tensile strength: 150 kN/m**

**Bearing Resistance against Puncturing: 180 kN (P33) / 240 kN (P66)**

**Bearing Resistance against Slope-Parallel Tensile Stress: 30 kN (P33) / 45 kN (P66)**

**High tensile steel mesh system for retaining of unstable slopes.**

**ETA 17/0118**  
**1301 - CPR - 1274**

**EAD 230025-00-0106**  
**Notified body: TSÚS (No. 1301)**

**[www.geobrugg.com](http://www.geobrugg.com)**