



**A:** Upper support rope Ø22 mm with 4 brake rings GS-8002

**B:** Lower support rope Ø22 mm with 4 brake rings GS-8002

**C:** Lateral anchor rope Ø22 mm

**D:** Retaining rope Ø22 mm with 1 brake ring GS-8002

**F:** Vertical rope Ø22 mm Geobinex



This document is proprietary to GEOBRUGG AG and is copyrighted with all rights reserved. It may not in whole or in part, be distributed, copied in any form, translated or otherwise reproduced in any form.

This document will not be exchanged, when being modified.

|                                   |     |                                       |          |                  |
|-----------------------------------|-----|---------------------------------------|----------|------------------|
| Modification:                     | M:% | Substitute for: GD-1012e ed. 22.05.17 |          |                  |
|                                   |     | Replaced by:                          |          |                  |
| <b>SL-150</b>                     |     | Drawn                                 | 18.07.17 | BIH              |
| <b>Rope assembly</b>              |     | Checked                               | 18.07.17 | BIH              |
| <b>WSL Test Rep. 10-17</b>        |     | Approved                              | 18.07.17 | BRR              |
| GEOBRUGG AG<br>CH-8590 Romanshorn |     |                                       |          | <b>GD-1012 e</b> |