



QUEBRADA OSORIO, VENEZUELA

Hangmuren- und Murgangschutz

Quebrada Osorio

Hangmuren- und Murgangschutz

Projekt	Quebrada Osorio
Ort	La Guaira / Vargas
Land	Venezuela
Installationsjahr	2008
Kunde	-
Ausgangslage	-
Massnahme	In 1999 massive debris flow impacts destroyed settlements and infrastructure. According mitigation and protective measures were required due to prevailing high risk. Implementation of "multi- level" concept with 2 debris flow barriers (Barrier 1: Type VX, L 11 m x H 6 m and Barrier 2: Type UX, L 23 m x H 6 m) with anchorage in shist / loose rock / soil. Retention capacity: approx. 1700 to 2400 m ³ in total.
Geschützte Objekte	Gebäude
Systemhöhe	6.0 m
Systemlänge	11 m - 23 m
Rückhaltevermögen	- m ³

Für Fragen steht Ihnen unser Geobrugg Spezialist gerne zur Seite

Roger Moor

Country Manager Ost- und Zentralschweiz, Liechtenstein

Tel. +41 71 466 81 52

Mobil +41 78 783 46 81

Roger.Moor@geobrugg.com



Geobrugg

info@geobrugg.com | www.geobrugg.com
