

DECLARATION OF PERFORMANCE FOR THE PRODUCT GBE-500A-R 1301 - CPR - 1172

Unique identification code of the product type:

Rockfall Protection Barrier GBE-500A-R, System Drawing GS-1122 / GS-1123

Intended use:

Falling Rock Protection Kit for use in civil engineering works to stop moving rock blocks with maximum energy of 500 kJ

Manufacturer:

Geobrugg AG

Aachstrasse 11

8590 Romanshorn

SWITZERLAND

System of assessment and verification of consistency of performance (AVCP):

System 1

European Assessment:

European Organisation for Technical Approvals: ETAG 027 (EAD 340059-00-0106)

European Technical Assessment: ETA 16/0329

Certificate of constancy of performance: 1301 - CPR - 1172

Notified body: TSÚS, Building Testing and Research Institute, Bratislava, Slovak Republic (No 1301)

Declared performance:

Energy level classification: 2

Maximum Energy Level (MEL): 500 kJ Service Energy Level (SEL): 170 kJ

Classification for residual height for MEL: Cat. A (> 50%)

Swiss Guideline / Federal Office of the Environment:

Specific Technical Documentation:

Manual incl. System drawing, maintenance manual, anchor forces

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

a. Roll

Signed for and on behalf of the manufacturer by

Armin Roduner, Technical Department

26.05.2020

Signature:





16

Geobrugg AG Aachstrasse 11, 8590 Romanshorn, SWITZERLAND

Rockfall Protection Barrier GBE-500A-R

Energy level classification: 2

Classification for residual height for MEL: Cat. A (> 50%)

Falling Rock Protection Kit for use in civil engineering works to stop moving rock blocks with maximum energy of 500 kJ

ETA 16/0329 1301 - CPR - 1172

ETAG 027 (EAD 340059-00-0106) Notified body: TSÚS (No. 1301)

www.geobrugg.com