

DECLARATION OF PERFORMANCE FOR THE PRODUCT UX060L - H4 1301 - CPR - 1301

Unique identification code of the product type:

High-Tensile Steel Wire Mesh System UX060L - H4, System drawing GD-1010

Intended use:

Retaining of debris flow with maximum impact pressure of 60 kN/m²

Manufacturer:

Geobrugg AG
Aachstrasse 11
8590 Romanshorn
SWITZERLAND

System of assessment and verification of consistency of performance (AVCP):

System 1

European Assessment:

European Organisation for Technical Approvals: EAD 340020-00-0106
European Technical Assessment: ETA 17/0275
CE Certificate of Conformity: 1301 - CPR - 1301
Notified body: TSÚS, Building Testing and Research Institute, Bratislava, Slovak Republic (No 1301)

Declared performance:

Dynamic pressure resistance: 60 kN/m²

Swiss Guideline / Federal Office of the Environment:

Specific technical documentation:

Manual incl. system drawing, maintenance manual anchor forces

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Armin Roduner, Technical Department

31.08.2023

Signature:





17

**Geobrugg AG
Aachstrasse 11, 8590 Romanshorn, SWITZERLAND**

**Shallow landslide barrier systems
UX060L - H4**

Dynamic pressure resistance: 60 kN/m²

Flexible Kits for retaining debris flows and shallow landslides/open hill debris flow

**ETA 17/0275
1301 - CPR - 1301**

**EAD 340020-00-0106
Notified body: TSÚS (No. 1301)**

www.geobrugg.com