

DECLARATION OF PERFORMANCE FOR THE PRODUCT SL-100 1301-CPR-1227

Unique identification code of the product type:

High-Tensile Steel Wire Mesh System SL-100, System drawing GD-1011

Intended use:

Retaining of debris flow with maximum impact pressure of 100 kN/m²

Manufacturer:

Geobrugg AG
Aachstrasse 11
8590 Romanshorn
SWITZERLAND

System of assessment and verification of consistency of performance (AVCP):

System 1

European Assessment:

European Organisation for Technical Approvals: EAD 340020-00-0106
European Technical Assessment: ETA 16/0448
CE Certificate of Conformity: 1301-CPR-1227
Notified body: TSÚS, Building Testing and Research Institute, Bratislava, Slovak Republic (No 1301)

Declared performance:

Dynamic pressure resistance: 100 kN/m²

Swiss Guideline / Federal Office of the Environment:

Specific technical documentation:

Manual incl. system drawing, maintenance manual anchor forces

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Armin Roduner, Technical Department

31.08.2023

Signature:





16

**Geobrugg AG
Aachstrasse 11, 8590 Romanshorn, SWITZERLAND**

**Shallow landslide barrier systems
SL-100**

Dynamic pressure resistance: 100 kN/m²

Flexible Kits for retaining debris flows and shallow landslides/open hill debris flow

**ETA 16/0448
1301-CPR-1227**

**EAD 340020-00-0106
Notified body: TSÚS (No. 1301)**

www.geobrugg.com