

TECHNICAL DATA SHEET


European Technical Assessment (ETA) ROCKFALL PROTECTION BARRIER RXE-3000



CERTIFICATION DETAILS

System Drawing No. / Rope Assembly No.	GS-1157 / GS-1158	Residual Height MEL / in % of tested height	3.53 m / 70%
Total absorbed energy until total stopping of the block	3591 kJ	Residual Height SEL 33% / in % of tested height	3.62 m / 72%
Kinetic energy of the block	3019 kJ	Elongation MEL (acc. to ETAG 027)	6.97 m
Energy Class acc. EAD-340059-00-0106	6	Braking Distance MEL (FOEN)	7.40 m
Energy Class acc. FOEN	8	Braking Distance SEL 50% (FOEN)	5.70 m
Swiss Guideline Certificate (FOEN)	FOEN S 14-4	Residual Height (category)	Cat. A (> 50%)
European Technical Assessment (ETA)	ETA 14/0362		
Certificate of constancy of performance	1301 - CPR - 1022	SYSTEM SPECIFICATION	
Certification Test Layout	vertical drop	Mesh Type / Net Type	ROCCO® 16/3/350
Weight of test body	9600 kg	LATERAL Characteristic Anchor Force	280 kN
Tested Heights	5.0 m	UPSLOPE ANCHOR ROPES Characteristic Anchor Force	230 kN
Certified Heights acc. ETA	5.0 - 6.0 m	Available heights	4.0 / 5.0 / 6.0 / 7.0 / 7.5 m
Certified Heights acc. FOEN	5.0 - 7.5 m	Post Spacing (min. / max.)	8 - 12 m

RXE-3000



Rockfall, slides, mudflows and avalanches are natural events and therefore cannot be calculated. This is why it is impossible to determine or guarantee absolute safety for persons and property with scientific methods. This means that to provide the protection we strive for, it is imperative to maintain and service protective systems regularly and appropriately. Moreover, the degree of protection can be diminished by events that exceed the absorption capacity of the system as calculated to good engineering practice, failure to use original parts or corrosion (i.e., from environmental pollution or other outside influences).