



WEISSSEE GLETSCHERBAHNEN, STUBACH BEI UTTENDORF (SALZBURG), AUSTRIA

Ochrona przed lawinami

Weißsee Gletscherbahnen, Stubach bei Uttendorf (Salzburg)

Ochrona przed lawinami

Projekt	Weißsee Gletscherbahnen, Stubach bei Uttendorf (Salzburg)
Lokalizacja	Uttendorf
Kraj	Austria
Rok Instalacji / montażu	2016
Inwestor	Weißsee Gletscherwelt GmbH
Projektant	Ingenieurkonsulent DDipl.-Ing. Stefan Oberndorfer
Wykonawca	Felbermayr Bau GmbH & Co KG, Abt. FST, Niederlassung Lienz

Opis sytuacyjny projektu

Falling rocks and weathering had damaged the previous wooden avalanche protection structure. The original protective function had to be restored. Furthermore, other hazardous areas had to be secured in order to provide better protection for the entire ropeway system.

In the project which was originally submitted, the intention was to construct massive avalanche wedges made of reinforced concrete. These were designed to directly protect double supports 21a and 21b, as well as support 22. On account of the enormous dimensions of this structure, the associated costs, and the considerable impact on the landscape – in a conservation area on the edge of the Hohe Tauern National Park, a new protection project was created.

Opis zastosowanego rozwiązania

The new protection concept combines three elements:

- permanent protection against avalanches through an avalanche protection structure made of snow nets
- temporary protection against avalanches through avalanche blasting in conjunction with
- an avalanche diversion dam to protect objects

Overall, eight sets of SPIDER® Avalanche snow nets with a total length of 140 meters are being erected in three potential avalanche starting zones. With this measure, it is only necessary to construct a 35-meter-long and approximately 3-meter-high dam made of locally acquired, heavy rubble.

With the hardly visible snow nets and natural dam, the authorities were extremely satisfied in terms of conservation of nature and the landscape.

Chroniony obiekt

Touristic infrastructure

Zabezpieczenie przeciwkorozyjne

Galvanized, GEOBRUGG SUPERCOATING

Długość systemu

8 m - 28 m

Wysokość efektywna (Dk, grubość pokrywy śnieżnej)

3.0

Gliding factor

2.5

W celu uzyskania dokładniejszych informacji skontaktuj się z naszym Przedstawicielem.

Kevin H. Coyle

Regional Manager Northeast

Telefon+1 860 377 3230

kevin.coyle@geobrugg.com



Geobrugg

info@geobrugg.com | www.geobrugg.com